


FH8537 : High Performance and Cost Effective, High Integration 2M ISP for CCTV

FH8537 is a new generation image signal processing chip for Parallel CIS (CMOS Image Sensor).It supports 2.0/1.3/1.0Mega image input, supports standard CVBS, 960H, 1280H and analog HD output, and built-in PMIC power module.It can be used in highly competitive industry analog HD cameras.


Features:

CIS Input	Support 2M/1.3M/1.0M CMOS sensor RGB / RGBIR 4X4 , 10bit data bit with Clock positive and negative edge sampling is configurable	Video Output	Standard CVBS (1280H) HD Analog : 1080P, 720P
ISP Function	High performance CFA interpolation Adaptive 2D and Y/C denoising AE/AWB Lens Shade Correction Image enhancement Automatic detection and elimination of dead pixels	Interface	I2C SPI UART GPIO SADC PWM
OSD Function	Customized T OSD/G OSD	Others	Work Temperature : -20°C ~ 70°C Power Supply: Analog 3.3V ; IO(3.3V or 1.8V) ; Digital (1.1V)
		Package	QFN56 (7*7mm)

Diagram:



Typical Application Solution:



联系我们:

上海富瀚微电子股份有限公司

地址: 上海市徐汇区宜山路717号6楼

邮编: 200233

电话: +86 21 6112 1558

传真: +86 21 6406 6786

邮件: Sales@fullhan.com

网址: www.fullhan.com

